



# SFR

## Downlight

SFR model downlight fixtures are indispensable application elements for interior lighting with their compact and simple structure. They can be applied in hotels, schools, shopping centers and many other places. Reflectors used in the fixture to perform this task without requiring extra frame and provide an appearance integrated with the ceiling and which does not harm the aesthetics structure of the area thanks to the fine structure thereof. They offer a perfect solution in locations where dark light is desired and glare is unwanted by using black reflector.



RAL COLORS

Std.  9016  
Opt.  9005

SFR

IP20  

Code	Luminous Flux	System Power	Weight
SFR13/S White	1.235 lm	13W	0.45 Kg
SFR13/S Black	1.090 lm	13W	0.45 Kg
SFR13/L White	1.200 lm	13W	0.45 Kg
SFR13/L Black	980 lm	13W	0.45 Kg

Body: Spun aluminum  
Reflector: PC

Driver: Included  
Voltage: 220~240 VAC


Color Temperature: 2700-3000-4000-5000-6500K  
Led: COB

ACCESSORY



Honeycomb Louvre

SFR 13/S



SFR 13/L



Code	Cut-Out
SFR13/S	Ø110 mm
SFR13/L	Ø105 mm




**BOX DIMENSIONS**  
SFR13/S 14x13x13 cm  
SFR13/L 16x13x13 cm




**BOX WEIGHT**  
SFR13/S 0.6 kg  
SFR13/L 0.6 kg

SFR 13/S White



SFR 13/S Black



cd/klm — C0 - C180 — C90 - C270 — C0 - C180 — C90 - C270