

Titan



Direct

Indirect
Luminaires

Titan model creates softly and warmly illuminated applications with indirect lighting. The lamps are concealed under the cover at the center of the reflector and the light reflects both on the front reflector in the middle of the cover and the wide base wavy type aluminum reflector. The double parabolic louvres on the front reflector add to the attractiveness of the fixture, besides allowing the light to concentrate on the application below it. The base reflector, on the other hand, develops a pleasant and uniform light distribution. Depending on the ambiance of choice, regular or perforated cover can be used. Perforated cover allows the light to diffuse on the ceiling and the walls to prevent complete darkness on the ceiling and minimize its contrast with the walls.

DIRECT-INDIRECT LUMINAIRES/ TITAN (PEG-PR)



PEG-PR/P



Description

Body: 0,6 mm thick, 6114, A1 quality DKP steel sheet is used in manufacturing. The body is coated with min. 80 micron thick epoxy polyester electrostatic powder paint. (Standard color RAL 9016)
Reflector: The reflectors in the fixtures are 0.4mm (99.9%) pure wavy type aluminum. It is equipped with double parabolic louvre.

Code

Lamp

Color

Modular or Plaster Ceiling

PEG-PR 236P 2x36W Dulux L
 PEG-PR 255P 2x55W Dulux L
 PEG-PR 214P 2x14W FH
 PEG-PR 224P 2x24W FQ

Clip-in Type

PEG-PR/002/236P 2x36W Dulux L
 PEG-PR/002/255P 2x55W Dulux L
 PEG-PR/002/214P 2x14W FH
 PEG-PR/002/224P 2x24W FQ

Box Dimensions


Inside box 1 PCS
 PEG-PR/P 610x670x90 mm

Cut-out: 575x575 mm

Weight

PEG-PR/P 5.400 gr

Protection: IP20



PEG-PR/D



Description

Body: 0,6 mm thick, 6114, A1 quality DKP steel sheet is used in manufacturing. The body is coated with min. 80 micron thick epoxy polyester electrostatic powder paint. (Standard color RAL 9016)
Reflector: The reflectors in the fixtures are made of 0.4mm thick (99.9%) pure wavy type aluminum. It is equipped with double parabolic louvre.

Code

Lamp

Color

Modular or Plaster Ceiling

PEG-PR 236D 2x36W Dulux L
 PEG-PR 255D 2x55W Dulux L
 PEG-PR 214D 2x14W FH
 PEG-PR 224D 2x24W FQ

Clip-in Type

PEG-PR/002/236D 2x36W Dulux L
 PEG-PR/002/255D 2x55W Dulux L
 PEG-PR/002/214D 2x14W FH
 PEG-PR/002/224D 2x24W FQ

Box Dimensions


Inside box 1 PCS
 PEG-PR/D 610x670x90 mm

Cut-out: 575x575 mm

Weight

PEG-PR/D 5.400 gr

Protection: IP20



Perforated cover: Inner part of the cover contains highly light permeable opal flexylens (SLP).

Dimensions

